

苏州金宝贝五金有限公司

Suzhou Gemic Hardware Co., Ltd

LAG SCREW SHIELD

- * Can be designed for light to medium duty fastening in concrete, mortar joint, masonry and brick.
- * Unique four-way expansion assures a tight grip even in out-of-round holes.
- * Short style for hard masonry, long style for soft.
- * The lag shield is rustproof, and is used with a lag screw to provide a dependable fixing.

SHORT TYPE

Code No.	Anchor Size	Drill \varnothing	Weight Kg/1000	Pull out Load kg	Qty (pcs) Box / Ctn
71AS20	1/4"	1/2"	11.7	250	50/500
71AS25	5/16"	1/2"	13.6	440	50/500
71AS30	3/8"	5/8"	28.5	640	50/500
71AS40	1/2"	3/4"	46.0	1240	50/500
71AS50	5/8"	7/8"	62.4	1280	25/125
71AS60	3/4"	1"	72.6	1640	25/125

LONG TYPE

Code No.	Anchor Size	Drill \varnothing	Weight Kg/1000	Pull out Load kg	Qty (pcs) Box / Ctn
71AL20	1/4"	1/2"	19.0	310	50/500
71AL25	5/16"	1/2"	19.3	620	50/500
71AL30	3/8"	5/8"	42.5	1100	50/500
71AL40	1/2"	3/4"	77.6	1670	50/500
71AL50	5/8"	7/8"	97.3	1730	25/125
71AL60	3/4"	1"	111.0	2020	25/125



LEAD WOOD SCREW ANCHOR

Lead wood screw anchors can be used in solid masonry and concrete, ideal for shallow hold anchoring-as it expands, lead flows into any irregularities in hole, making incorrect setting difficult.



Code Number	Anchor Size	Drill \varnothing	Weight Kg/1000	Pull out Load kg	Qty (pcs) Box / Ctn
72A0620	6-8x3/4"	1/4"	5.6	130	100/1000
72A0625	6-8x1"	1/4"	6.8	160	100/1000
72A0640	6-8x1-1/2"	1/4"	9.0	200	100/1000
72A1020	10-14x3/4"	5/16"	6.5	360	100/1000
72A1025	10-14x1"	5/16"	9.0	360	100/1000
72A1040	10-14x1-1/2"	5/16"	13.6	450	100/1000
72A1625	16-18x1"	3/8"	10.0	570	25/250
72A1640	16-18x1-1/2"	3/8"	20.4	570	25/250